


For reference only. See data sheet for the detailed specifications.

Technical Specification



Freq. Range(GHz)	2.0 – 18.0
Coupling(dB)	20
Accuracy(dB)	±0.5 Max.
Directivity	15 Min.
Insertion Loss(dB)	0.7 Max. (Not including the theoretical loss 0.04dB)
Mainline VSWR	1.40:1 Max.
Coupled VSWR	1.40:1 Max.
Average Power(W CW)	20 Max.
Peak Power(KW)	3
Connector	SMA-Female
Operating Temp.(°C)	-55~+85
Material	Al
Size(mm)	57.2 x 12.7 x 17.8
Net Weight(Kg)	0.06 Around

Outline Drawing (Size: mm)



AINFO Inc.

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,

Page 1 of 3


(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670


Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Test Results

Coupling



Directivity



Insertion Loss (Including the theoretical loss 0.04dB) & VSWR

