Technical Specification



Waveguide	WR4
Frequency Range(GHz)	183.0 – 240.0
Circular WG Dia.(mm)	1.168
Length (mm/inch)	27.9/1.1
Insertion Loss(dB)	0.6 Max.
VSWR	1.20:1 Max.
Circular Waveguide Flange	UG-387/U-M
Rectangular Waveguide Flange	FUGP2200(UG-387/U-M)
Material	Cu
Size(mm)	27.9 x 19.1 x 19.1
Net Weight(Kg)	0.02 Around

Outline Drawing (Size: mm)



China(Beijing): Tel: (+86) 10-6266-7326, (+86) 10-6266-7327 Fax: (+86) 10-6266-7379
China(Chengdu): Tel: (+86) 28-8519-2786, (+86) 28-8519-3044 Fax: (+86) 28-8519-3068 Website: www.ainfoinc.com
USA : Tel: (+1) 949-639-9688, (+1) 949-639-9608 Fax: (+1) 949-639-9670 Email: sales@ainfoinc.com

Data subject to change without notice. For current data sheets, please contact: Sales@ainfoinc.com

Flange Outline Drawing (Size: mm)



UG-387/U-M



UG-387/U-M

China(Beijing): Tel: (+86) 10-6266-7326, (+86) 10-6266-7327 Fax: (+86) 10-6266-7379
China(Chengdu): Tel: (+86) 28-8519-2786, (+86) 28-8519-3044 Fax: (+86) 28-8519-3068 Website: www.ainfoinc.com
USA : Tel: (+1) 949-639-9688, (+1) 949-639-9608 Fax: (+1) 949-639-9670 Email: sales@ainfoinc.com

Data subject to change without notice. For current data sheets, please contact: Sales@ainfoinc.com