



Technical Specification



Frequency Range(GHz)	2.0 – 18.0
Input VSWR	1.40:1 Max.
Output VSWR	1.40:1 Max.
Insertion Loss(dB)	1.0 Max.
Isolation(dB)	18 Min.
Amplitude Balance(dB)	±0.3 Max.
Phase Balance(°)	±3 Max.
Average Power(W)	20 Max.
Peak Power(KW)	3
Connector	SMA-Female
Operating Temp.(°C)	-55~+85
Material	Al
Size(mm)	26.4 x 12.7 x 45.5
N.W.(Kg)	0.05 Around

Outline Drawing (Size: mm)



AINFO Inc.

Page 1 of 3

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,


(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670


Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Test Results

I.L. & VSWR



Isolation



Amplitude Balance & Phase Balance & VSWR

