


Technical Specification



EIA WRD	WRD750
Switch Type	DPDT Latching
Frequency Range(GHz)	7.5 - 18.0
DC Power Supply(V)	27 ± 3
Current(A)	1.0 Max.
VSWR	1.20:1 Max.
Isolation(dB)	60 Min.
Insertion Loss(dB)	0.5 Max.
Switching Speed(ms)	110 Max.
Average Power(W CW)	500 Max.
Flange	FPWRD750D24 (Modified with 4x 6-32UNC-2B D5)
Operating Temperature(°C)	-55 ~ +85
Material	Al
Finish	Chemical Conversion Coating, Black Paint
Size(mm)	57.15 x 70.4 x 150.25
Net Weight(Kg)	0.86 Around

Outline Drawing (Size: mm)



AINFO Inc.

Page 1 of 8

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,

(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608


Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Flange Drawing (Size: mm)


FPWRD750D24

(With two through mounting holes
and two screws holes)




Test Results


I.L.(From port 1 to port 2) @Pos. 1




I.L.(From port 3 to port 4) @Pos. 1




Iso.(From port 1 to port 3) @ Pos. 1




Iso.(From port 1 to port 4) @ Pos. 1







Iso.(From port 2 to port 3) @ Pos. 1




Iso.(From port 2 to port 4) @ Pos. 1



I.L. (From port 1 to port 3) @ Pos. 2

I.L. (From port 2 to port 4) @ Pos. 2


Iso.(From port 1 to port 2) @ Pos. 2

Iso.(From port 1 to port 4) @ Pos. 2


Iso.(From port 3 to port 2) @ Pos. 2



Iso.(From port 3 to port 4) @ Pos. 2

