



For reference only. See data sheet for the detailed specifications.

Technical Specification

28EWG-T64



28EWG-T64-A1



Frequency Range(GHz)	22.5 – 45.0
Waveguide	WR28
Gain(dBi)	8 Typ.
Polarization	Dual Linear
3dB Beamwidth(deg)	E Plane: 59 Typ.
	H Plane: 66 Typ.
Cross Pol. Isolation(dB)	35 Typ.
Port to Port Isolation(dB)	45 Typ.
VSWR	2.0:1 Typ.
Output	FBP320(UBR320) (Modified with 4xM3 Deep5)
Material	Cu
Finish	Gold Plated, Silver Plated and Chemical Conversion Coating, Gray Paint
Size(mm)	28EWG-T64: 101.6 x 101.6 x 264.2
	28EWG-T64-A1: 399.6 x 399.6 x 264.2
Net Weight(Kg)	28EWG-T64: 0.49 Around
	28EWG-T64-A1: 2.63 Around

PATENT ID (US)


US 11031692, US 10871511

PATENT ID (China)

ZL202020594309.9, ZL202120369753.5

Outline Drawing (Size: mm)

FBP320 Output(P/N: 28EWG-T64)



AINFO Inc.

China(Beijing):
China(Chengdu):
USA :


Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,

(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608


Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com


FBP320 Output with Round Mounting Bracket (Option, P/N: EWG-MB40)




FBP320 Output with L Type Mounting Bracket (Option, P/N: EWG-L30/FRP)




FBP320 Output, Equipped with Absorber (Option, P/N: 28EWG-T64-A1)



FBP320 Output with Round Mounting Bracket & Equipped with Absorber (Option, P/N: EWG-MB40 & 28EWG-T64-A1)



FB320 Output with L Type Mounting Bracket & Equipped with Absorber (Option, P/N: EWG-L40 & 28EWG-T64-A1)



AINFO Inc.

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,


(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608

Page 4 of 16

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Flange Drawing (Size: mm)



FBP320

AINFO Inc.

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,



(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670


Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Test Results


1. Gain & Antenna Factor



2. Cross Polarization Isolation




3. Port to Port Isolation




4. VSWR


Port-H



Port-V



5. Pattern



AINFO Inc.

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,

(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608

Page 9 of 16

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com

