


For reference only. See data sheet for the detailed specifications.

Technical Specification




EIA WR	WR28
Frequency Range(GHz)	32.0 – 38.0
Insertion Loss(dB)	0.2 Max.
VSWR	1.15:1 Max.
Isolation(dB)	20 Min.
Amplitude Balance(dB)	±0.5 Max.
Phase Balance(°)	±2 Max.
Peak Power(KW)	4
Flange	FBP320(UBR320) (Modified with 4xM3 Deep4)
Material	Cu
Size(mm)	66.04 x 32 x 21.66
Net Weight(Kg)	0.35 Around

PATENT ID (China)

ZL202210848290.X, ZL202221858194.5,
ZL202230459987.9

Outline Drawing (Size: mm)



AINFO Inc.

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,


Page 1 of 4

(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Flange Drawing (Size: mm)



FBP320

AINFO Inc.

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,


(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670


Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Test Results

I.L. & VSWR



Isolation



Amplitude Balance & Phase Balance & VSWR

