
2.4mm In-Series Adapters

Performance Features
Nominal Impedance: 50ohm
Frequency Range: DC-50GHz
Durability: 500cycles
Operating Temperature: -55ºC ~ +165ºC


Materials/Finishes
Housing: Type 303 Stainless Steel – Polished & Passivated
Center Contact: Beryllium Copper Plated Gold (MIL-G-45204)
Insulators: PEI
Interfaces: IEEE STD 287-2007






P/N	HPA115-01
Description	2.4mm/Female-2.4mm/Female
VSWR	DC-50GHz...1.20:1 max






P/N	HPA115-02
Description	2.4mm/Male-2.4mm/Female
VSWR	DC-50GHz...1.15:1 max





P/N	HPA115-03
Description	2.4mm/Male-2.4mm/Male
VSWR	DC-50GHz...1.15:1 max





P/N	HPA115-04
Description	2.4mm/Female-2.4mm/Female
VSWR	DC-50GHz...1.20:1 max

China(Beijing): Tel: (+86) 10-6266-7326, (+86) 10-6266-7327 Fax: (+86) 10-6266-7379
China(Chengdu): Tel: (+86) 28-8519-2786, (+86) 28-8519-3044 Fax: (+86) 28-8519-3068
USA : Tel: (+1) 949-639-9688, (+1) 949-639-9608 Fax: (+1) 949-639-9670
Website: www.ainfoinc.com
Email: sales@ainfoinc.com