



For reference only. See data sheet for the detailed specifications.

Technical Specification



Freq. Range(GHz)	4.0 – 18.0
Coupling(dB)	30
Accuracy(dB)	±1.0 Max.
Directivity(dB)	12 Min.
Insertion Loss(dB)	1.0 Max. (Not including the theoretical loss 4.35×10^{-3} dB)
Mainline VSWR	1.50:1 Max.
Coupled VSWR	1.50:1 Max.
Average Power(W CW)	20
Peak Power(KW)	3
Connector	SMA-Female
Operating Temp.(°C)	-55 ~ +85
Material	Al
Size(mm)	43 x 12.3 x 18
Net Weight(Kg)	0.04 Around

Outline Drawing (Size: mm)



AINFO Inc.

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,

Page 1 of 3


(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670


Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Test Results

Coupling & VSWR



Directivity



Insertion Loss(Including the theoretical loss 4.35×10^{-3} dB) & VSWR

